# **Product data sheet**

Specifications



# Power Cord, C13 to C14, 2.5m

AP9870



#### **Overview**

Lead time Usually in Stock

#### Main

Input Connection Type	IEC 60320 C14
Cable length	2.50 m
Number of cables	1

#### **Physical**

Colour	Black
Height	3.8 cm
Width	7.6 cm
Depth	20.3 cm
Product weight	0.23 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Network frequency	50/60 Hz
Permissible voltage	90250 V
Max line current	10 A
Input current limits	10 A

#### **Output**

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Protection type	Without circuit breaker

#### Conformance

Product certifications

CSA

UL listed

VDE

#### **Environmental**

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	10.2 cm
Package 1 Length	20.3 cm
Package 1 Weight	0.3 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	25 cm
Package 2 Width	35 cm
Package 2 Length	56 cm
Package 2 Weight	9.1 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	25
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	9.1 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### **Contractual warranty**

Warranty

2 years repair or replace

Recommended replacement(s)