

Product datasheet

Specifications



APC Smart-UPS C, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+1x IEC C19 outlets, USB and Serial communication, AVR, Graphic LCD

SMC3000I

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
--------------	---

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Rated power in W	2100 W
Rated power in VA	3000 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 320 C20
Output connection type	8 IEC 320 C13 1 IEC 320 C19
Number of rack unit	0U
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD USB cable

Batteries & Runtime

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	APCRBC150
Battery power in VAh	552 VAh runtime
Battery charger power	183 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Entry level
Redundant	No

Physical

Colour	Black
Height	43.5 cm
Width	19.7 cm
Depth	54.4 cm
Product weight	43 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Input voltage limits	170...300 V adjustable 180...287 V
Network frequency	47...63 Hz

Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50 Hz sync to mains

Conformance

Product certifications	C-Tick CE EAC GOST SABS VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	45 dBA
Heat dissipation	135 Btu/h
Operating altitude	0...10000 ft

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control panel	Multifunction LCD status and control console
Free slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	76.2 cm
Package 1 Width	69.9 cm
Package 1 Length	38.1 cm
Package 1 Weight	51 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)