

# SFP-3001, 1.25Gbps Multi-mode SFP Transceiver, 550m, 850nm

## Product Images

---



## Short Description

---

- IEEE 802.3z Gigabit Ethernet compliant
- Supports Digital Diagnostics Monitoring (DDM) for easy status monitoring
- Provides duplex LC connector
- Hot-swappable
- RoHS compliant and Lead Free
- Compatible with SFP Multi-Sourcing Agreement (MSA) standards

## Description

---

LevelOne SFP-3001 is a high performance and cost-effective multi-mode SFP transceiver. Intended for use with Gigabit Ethernet, it provides up to 1.25 Gbps bi-directional data transfer rate on a single duplex fiber core. For use with 50 and 125 micron fiber cables, it can reach a distance of up to 550 meters. The SFP-3001 transceiver operates using a wavelength of 850nm with a VCSEL Laser Diode light source and has an LC port.

## Additional Information

---

Gigabit multi-mode LC	1
Color	Silver
EAN	4015867154663
Model Number	SFP-3001
Features	Hot-swappable 50/125 $\mu$ m Multi-mode Fiber
Grade	Commercial
Transceiver Type	SFP
Fiber Optical Mode	Multi-Mode
Approval and Compliance	EMC Directive 2014/53/EU IEC 61000-4-3 / IEC 61000-4-2 , MIL-STD-883 Method 3015" EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B. Class 1 Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC)60825-1,2" RoHS Directive 2011/65/EU SFP Multi-Sourcing Agreement(MSA) SFP MSA SFF-8074i Compliant
Operating humidity	0% RH ~ 85% RH
Operating temperature	0°C ~ 70°C
Storage temperature	-40°C ~ 85°C
Package Contents	SFP-3001, Quick Installation Guide
Receiver sensitivity	-18dBm
Dimensions (W x D x H)	13.7 x 57 x 12 mm
Product weight (kg)	0,02
Standards	IEEE 802.3z 1000Base-SX
Data rate	Up to 1.25Gb/s data links
Link power budget (dB)	9dB
Wavelength (nm)	850
Power input	3.3V / 250mA
Power consumption	800mW
Optical transmission power (dBm)	-9 to -4 dBm

