

APC Smart-UPS, Line Interactive, 750VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT750RMI2UC

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable ru Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.	
Lead Time	Usually in Stock	
Main		
Main Input Voltage	230 V	
Other Input Voltage	220 V 240 V	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated Power In W	500 W	
Rated Power In Va	750 VA	
Input Connection Type	IEC 320 C14	
Output Connection Type	4 IEC 320 C13 2 IEC Jumpers	
Number Of Rack Unit	2U	
Number Of Cables	1	
Battery Type	Lead-acid battery	
Provided Equipment	Documentation CD Installation guide Rack mounting support rails USB cable	

Complementary

Software Package	SmartConnect software for remote power monitoring feature availability varies by
	terms of use

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0

Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Battery Life	46 year(s)
Replacement Battery	APCRBC123 ☐
Battery Charger Power	56 W rated

General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

Physical

•	
Colour	Black
Height	8.6 cm
Width	43.2 cm
Depth	40.9 cm
Net Weight	16.6 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes

Input

Input Voltage Limits	151302 V adjustable 160286 V	
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing	

Output

Harmonic Distortion	Less than 5 %
Maximum Configurable Power In Va	750 VA
Maximum Configurable Power In W	500 W
Transfer Time	6 ms typical : 10 ms maximum
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	CE		
	EAC		
	RCM		
	TÜV		
	VDE		

 Standards
 EN/IEC 62040-1:2019/A11:2021

 EN/IEC 62040-2:2006/AC:2006

EN/IEC 62040-2:2018

Environmental

Acoustic Level	42 dBA
Heat Dissipation	46 Btu/h
Operating Altitude	010000 ft
Ambient Air Temperature For Operation	040 °C
Ambient Air Temperature For Storage	-1545 °C
Storage Altitude	0.0015240.00 m
Relative Humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Control Panel	Multifunction LCD status and control console	
Emergency Power Off	Optional	
Free Slots	1	
Communication Port Support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use	
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays	

Surge Protection and Filtering

Surge Energy Rate	459 J
Noise Suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	58.4 cm
Package 1 Length	54.6 cm
Package 1 Weight	21.23 kg

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information