

ML1708

17" LCD KVM Switch (Single Rail, VGA Series)

NEXIS



- Front LCD Console (Keyboard, Mouse, 17" monitor) + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- IP optional (IP card could be installed inside KVM module);
- Extra prepositive USB mouse interface;
- Single port length: 462.6mm; Multi-ports length: 611mm

SPECIFICATION

17" LCD Console

Type	17" LCD Console	
LCD Monitor	Ratio	4:3
	Video	SXGA TFT-LCD
	Visible Square	337.920(H) × 270.336(V)
	Resolution	1280x1024@60HZ (Opitmum) /1920x1200@60HZ(Max)
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264x0.297mm
	LED MTBF	100,000 hours
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible	Windows Me/NT/2000/XP, WIN7, Server2003, WIN8/8.1, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Pad
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Dimension	407x445x45mm	
Weight	6.15kg	

KVM Module

Type	8 Port KVM Switch	
Computer Connection	Direct	8
	Max.	128
CPU Port Selection	OSD, Front button, Hotkey, IP Remote (optional)	
Connectors	Console	DB 37 pin
	Computer	8 x VGA DB15, Female
	Power	1 x DC Jack
	Network Port	1 x RJ45(Optional)
Switch	Port Selection	KVM Panel Digital keys
	KVM Reset	KVM Panel Function keys
	IP Module Reset	1 x semi-embedded key
	IP Module Default	1 x semi-embedded key
LED's	Selected	Nixie Tube Display
Using	Online	8 x Red
Using	IP Network	1 x Green, 1 x Orange
Analog Mode	Keyboard/Mouse	USB, PS/2
Resolution (Max)	1920x1200@60HZ	
Scan time interval	3, 5, 10, 15, 20, 30, 40, 60s (3s by default)	
Operation Environment	Operating Temp.	-10-50°C
	Storage Temp.	-20-60°C
	Humidity	0-80%RH, No Condensation
Physical Properties	Housing	Metal
	Dimension	148.4x445x45mm
	Weight	3.32kg



สำนักงานใหญ่ 88/8 ถนนพหลโยธิน กทม. โทร. 02-459-1111
@Curve Mall เชียงใหม่ โทร. 053-273-133

mc.co.th

@macrocare

Macrocare

Macrocare_th