

ML1908

19" LCD KVM Switch (Single Rail, VGA Series)

NEXIS



- Front LCD Console (Keyboard, Mouse, 19" monitor) + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- IP optional (IP card could be installed inside KVM module);
- Extra prepositive USB mouse interface;
- Single port length: 462.6mm; Multi-ports length: 611mm

SPECIFICATION

19" LCD Console

Type		18.51" LCD Console
LCD Monitor	Ratio	16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	409.8(H) × 230.4(V)
	Resolution	1366x768@60HZ (Optimum) /1920x1080@60HZ(Max)
	Support Color	16.7M True 8 bit
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	300x300um
	LED MTBF	100,000 hours
	Input Power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible	Windows Me/NT/2000/XP, WIN7, Server2003, WIN8/8.1, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Pad
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Dimension		407x445x45mm
Weight		6.07kg

KVM Module

Type		8 Port KVM Switch
Computer Connection	Direct	8
	Max.	128
CPU Port Selection		OSD, Front button, Hotkey, IP Remote (optional)
Connectors	Console	DB 37 pin
	Computer	8 x VGA DB15, Female
	Power	1 x DC Jack
	Network Port	1 x RJ45(Optional)
Switch	Port Selection	KVM Panel Digital keys
	KVM Reset	KVM Panel Function keys
	IP Module Reset	1 x semi-embedded key
	IP Module Default	1 x semi-embedded key
LED's	Selected	Nixie Tube Display
Using	Online	8 x Red
Using	IP Network	1 x Green, 1 x Orange
Analog Mode	Keyboard/Mouse	USB, PS/2
Resolution (Max)		1920x1200@60HZ
Scan time interval		3, 5, 10, 15, 20, 30, 40, 60s (3s by default)
Operation Environment	Operating Temp.	-10-50°C
	Storage Temp.	-20-60°C
	Humidity	0-80%RH, No Condensation
Physical Properties	Housing	Metal
	Dimension	148.4x445x45mm
	Weight	3.32kg



สำนักงานใหญ่ 88/8 ถนนพหลโยธิน ถนน. โทร. 02-459-1111
@Curve Mall เชียงใหม่ โทร. 053-273-133

mc.co.th

@macrocare

Macrocare

Macrocare_th